



Finnaren & Haley Paints

Technical Data

Lenox Satin Gloss Acrylic Enamel

SKU: 540000

Interior Use Only 0505

Description

Lenox is a top quality, washable, non-yellowing, spatter resistant satin gloss enamel. It combines all the features of a flat wall paint and the marvelous features of a low gloss enamel. It is recommended for use on interior walls, trim, kitchens, bathrooms, and anywhere frequent cleaning is required, and a soft sheen is desired.

Technical Data(typical)

Type	Acrylic / Acrylic Copolymer Latex
Theoretical Coverage	557 sq. ft./gal. per dry mil
Recommended DFT per Coat	1.0-1.4 mils DFT
Gloss	Satin Gloss
Weight per Gallon	10.0 ± 0.2 lbs.
Viscosity	90-95 KU
Solid: by Volume	34.7 ± 1%
by Weight	44.0 ± 1%
VOC	1.24 lbs/gal max (150 g/l)
Flash Point	None
Color	White, Bases: W, M, D, A See Millennium Fan Deck
Packaging	Quarts, Gallons, 5-Gallon

Surface Preparation

Clean surfaces of all dirt, oil, grease, powdering plaster, glue size, paste, or other surface contaminants with a household detergent such as Soilax. Rinse surface thoroughly with water. Scrape away all loose, scaly paint; dull all glossy surfaces with light sanding or liquid deglosser. New plaster, concrete, and mortar should cure 30 days, with good ventilation or heat, if necessary, before painting. Spackle all nail holes and sand smooth. If painting metal, remove all rust and scale before priming. Seal all water soluble bleeding stains with Stain Kill or Master Primer before finish coating. If mildew is present, remove completely by sterilizing the surface with mildew remover before painting, following the directions on the package.

Primers

NEW DRYWALL or MASONRY should be primed with T.C.D. Primer (715100). New plaster must be cured for 30 days.

Note: Some drywall is made with recycled paper which sometimes stains when painted. If this happens, prime the surface with Stain Kill primer (719100) and then finish coat.

NEW WOOD should be primed with TCD Primer (715100) or Master Primer (728100).

CONCRETE BLOCK should first be coated to fill the voids with Ready Mixed Block Filler (751100).

METAL: Ferrous: Prime with Corrosion Fighter (723300)

Galvanized or Aluminum: High Performance Acrylic Polyurethane Primer (675750)

PREVIOUSLY PAINTED SURFACES: Spot or full prime as needed and then paint with 1 or 2 coats of **Lenox Satin Gloss Acrylic Enamel**.

Finnaren & Haley, Inc.; Corporate Office and Manufacturing

901 Washington St., Conshohocken, PA 19428

For additional information or technical assistance please call:

1-800-843-9800 or fax to (610)825-1184



Lenox Satin Gloss Acrylic Enamel

SKU: 540000

Thinning

Brush, Roller or Airless Spray Application: This product can be thinned with water up to 4 oz. Per gal.

Application

Apply by brush, roll, or airless spray. Stir with a gentle lifting motion. If rolling, apply the paint generously in an “M” shape about two feet square, then fill in with arched cross strokes finishing up and down. Keep a ‘wet edge’ to avoid ridging and overspreading. Cut in the edges with a synthetic bristle brush as you proceed with rolling. Complete one wall at a time and never stop in the middle of a wall.

Recommended Spread Rate

400 square feet per gallon, approximately. Some surfaces may require more depending on the porosity.

Clean Up

Clean up all tools and equipment promptly with warm soapy water. Flush spray equipment with paint thinner or mineral spirits to prevent rusting.

Drying Time

@ 77 degrees with 50% R.H.

To Touch: 2 hours

To Recoat: 16-24 hours

Special Information

Lenox has very good “block resistance”. Allow one week before placing books, plants, etc. on the dry film. Do not apply if the surface temperature is below 50 degrees F. or if condensation is present.

KEEP THE PAINT FROM FREEZING!

Not recommended over wallpaper. Vinyl wall coverings can lose adhesion. Remove the old wallpaper and clean the old glue off before repainting.

Glue size must be removed from the surface before painting by washing with clean warm water and allowed to dry. When more than one can of the same color is used, “box” or intermix the cans prior to painting to assure maximum color uniformity.

After application, allow two weeks before washing. Use a sponge with warm water in a mild solution of non-abrasive detergent.

When touching-up, use the same application tool which was originally used to produce the same finish.

Right to Know & Safety

The label complies with all applicable Right to Know laws. For information on safety hazards associated with this product please refer to MSDS sheets.

Warranty

This product will perform as claimed if directions are followed. Since we cannot control conditions or methods of use, the warranty is limited to replacement or refund value of this product actually used. This warranty does not include labor or labor costs.

STORE LOCATIONS: PHILADELPHIA: Castor Ave (215)745-8020, Magee St (215)332-0700, Oregon Ave (215)462-8027

PENNSYLVANIA: Allentown (610)821-1304, Ardmore (610)642-3223, Doylestown (267)880-1644, Drexel Hill (610)789-6141, Exton (610)363-2245, Feasterville (610)355-8282, Flourtown (215)836-7551, Folsom (610)586-0100, Lancaster (717)560-9940, Norristown (610)279-2714, Paoli (610)647-6663, Pottstown (610)326-0959, West Chester (610)692-0700, Willow Grove (215)659-7707; **NEW JERSEY:** Asbury Pk (732)775-5653, Bloomfield (973)743-1211, Cape May (609)463-0074, Cherry Hill (609)665-1138, Hamilton Square (609)588-0919, Kearny (201)991-2606, Mt. Ephraim (609)931-2745, Somers Point (609)926-7727, Turnersville (609)228-6885, **DELAWARE:** Newark (302)738-1940.